

# WASTOP® INLINE CHECK VALVE

## WaStop 340

<b>Model Name</b>	WS340
<b>Nominal Diameter</b>	DN 350
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Gasket Mtrl.</b>	EPDM
<b>Weight [kg]</b>	16.5
<b>Min. ID Host Pipe [mm]</b>	344
<b>Max. ID Host Pipe [mm]</b>	360
<b>Max. Flow Vel. [m/s]</b>	3
<b>Max. Flow Vol. [l/s]</b>	290

## Product Variants

<b>Art. No</b>	<b>WS340-S3-316</b>
<b>Membrane mtrl.</b>	Polyurethane
<b>Valve Body mtrl.</b>	EN 1.4404
<b>Max. Back Pressure [mmH<sub>2</sub>O]</b>	5
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	380
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	220
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	205
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	60
<b>Vertical Opening [mmH<sub>2</sub>O]</b>	350
<b>Vertical Closing [mmH<sub>2</sub>O]</b>	205

